

INTERIM RESTORATIVE

Walk Behind Extractors AV 18AX

With large 18 gallon tanks and a 3/4 hp drive motor, the Avenger AV 18AX can tackle the biggest commercial jobs. Other key features include rotationally molded polyethylene tanks and an easy-access removable spray bar with twist-off jets. The powerful 1.8 hp, three-stage vacuum motor provides 135" water lift and 95 cfm of airflow while the 130 psi pump allows for a variable flow rate up to 1.2 gpm.

With the optional patented onboard "Smart Kit", the pump can be used as an automatic pre-spray system with the chemical injected downstream (of the pump) so only water flows through it, preventing any buildup. With the Smart Kit, no mixing of chemicals is required and the dilution is always correct. It also allows the unit to be used in "low-flow mode" for interim cleaning and faster drying times. The efficient forward motion allows upwards of 4,000 sq. ft. per hour to be cleaned—three times the rate of pullback self-contained units. The spring loaded vacuum shoe ensures consistent pressure and excellent soil recovery at all times.



AV 18AX



MODEL

AV 18AX

Vacuum Motor	1400 W, 1.8 hp, 3 stage
Airflow	95 cfm
Water Lift	135"
Brush Motor	100 W / .13 Hp
Brush Speed	600 rpm
Drive Motor	0.75 hp
Cleaning Width	20"
Pump Type	diaphragm w/bypass
Weight	143 lb
Power Cord	50'

Capacity: Solution	18 gal.
Capacity: Recovery	18 gal.
Pump: Power	100 W
Pump: Pressure	130 psi
Pump: Flow	0–1.2 gpm
Working Capacity	4,000 sq. ft. / hr.



www.nacecare.com

✉ sales@nacecare.com ☎ 905.795.0122