



Quick Links

[Facilities Website](#)

[Safety Data Sheets \(SDS\)](#)

Some of these links lead to web-based resources that are not product-specific.

Product Description

3M™ Top Line Speed Burnish Pad 3200 is a floor maintenance burnishing pad made of high quality synthetic fibers in a non-woven web construction. The fibers are bonded to the web structure with a durable resin system that permeates the entire pad. Unique design and durable construction make these pads the industry standard for consistent performance and long life.

- Designed to be used as part of the 3M™ TopLine System or for dry burnishing
- For use on ultra high speed floor machines operating at 1500 - 3000 rpm

Applications

This product is used on corded electric, battery electric, or propane powered floor machines for burnishing a wide variety of floor finishes. This pad may be used for burnishing as part of the 3M™ TopLine system along with 3M™ TopLine Conditioner and 3M™ TopLine Pre-Burnish Pad.

For use on finish-coated flooring such as sheet vinyl, vinyl tile, marble, terrazzo or concrete.

Features and Benefits

Uniform coating throughout every 3M™ floor pad reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life.

Pads are reversible and will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance.

Exact standards for quality mean thickness uniformity from edge to edge and pad to pad are exceptional, resulting in consistent performance without pad wobble or machine vibration. The precise center-hole placement and roundness of the pads also contributes to the smooth operation which extends pad life and may help reduce operator fatigue.

Packaging and Marking

Each carton shall be labeled to identify the contents by product name, size, quantity and manufacturer. Each pad shall be printed with the manufacturer's name.

Standard Sizes

Circular discs and other shapes are available in a variety of common sizes. Pads are nominally one inch thick.

Pad Use and Cleaning

Dust mop floor prior to performing 3M™ TopLine floor care procedure. Clean and condition floor by mop applying the 3M™ TopLine Conditioner or scrubbing with an automatic scrubber or rotary floor machine. Burnish floor to a high gloss with 3M™ TopLine Speed Burnish Pad 3200.

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent solution to dissolve caked soil or finish prior to hosing out.

Storage

Store indoors in original packaging and under normal facility conditions.

Product Characteristics

3M™ Top Line Speed Burnish Pad 3200		Test Method
Fiber Type	Polyester	N/A
Weight (4 in. by 6 in.)	18.6 g	CCD0015
O.D. Dimension	Designated Size ± 1/16 in.	CCD0004
Thickness	1 in. nominal	CCD0002
Alkali Resistance (Tensile Retention)	44%	CCD0005,6
Aggressiveness	NA	CCD0020
Packaging Recycle Content	50-100% recycled content	N/A

Explanation of Signal Word Consequences**DANGER**

Indicates a hazardous situation which, if not avoided, will result in serious injury or death.

**WARNING**

Indicates a hazardous situation which, if not avoided, could result in serious injury or death.

**DANGER**

To reduce the risks associated with inhalation of or exposure to contaminants:

- DO NOT use this product on any asbestos-containing material.

**WARNING**

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

Health and Safety**CAUTION**

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to 3M.com/SDS, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical

information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the **Customer Service Department at 1-800-852-9722**.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Commercial Solutions

3M Center, Building 220-12E-04
St. Paul, MN 55144

1-800-852-9722
3M.com/Facility

© 3M 2020. All rights reserved.
3M is the trademark of 3M.
Used under license in Canada.
All other trademarks are property of their respective owners.
Revision B, May 2020 Please recycle.

3M Science.
Applied to Life.™

Maintenance Operation
Equipment Speed
First Choice
Alternate Choices
Stripping

To remove finish, sealer and contaminants from the floor surface.

Rotary or Automatic
Low Speed
175-600 RPM

Scrubbing

To provide a fresh new surface for finishing.

Rotary or Automatic
Low Speed
175-600 RPM

Cleaning

To remove light soil and other contaminants.

Rotary or Automatic
Low Speed
175-600 RPM

Buffing

To remove scuffs and black heel marks and enhance floor appearance.

Rotary
Low Speed
175-600 RPM

Burnishing

To remove scuffs and marks, repair finish and improve gloss and image clarity.

Electric, Battery, Propane
Ultra High Speed
1500 RPM & Above

Best Gloss

Electric, Battery, Propane
Ultra High Speed
1500 RPM & Above

Soft Finish

Electric, Battery, Propane
Ultra High Speed
1500 RPM & Above

Stone Floor Conditioning

To clean and condition worn and dull stone floors.

Rotary, Automatic, Electric, Battery or Propane
Low to Ultra High Speed
175-1500 RPM & Above

Stone Floor Polishing

To clean and polish stone floors with medium shine in good condition.

Rotary, Automatic, Electric, Battery or Propane
Low to Ultra High Speed
175-1500 RPM & Above



3M™ High Productivity Pad 7300
Our most aggressive stripping pad. Unique open construction resists loading and clogging. For fast removal of finish and proven consistent stripping.



Scotch-Brite™ Surface Preparation Pad Plus
Long-lasting, high performance scrubbing pad for top coat removal prior to recoating.



Scotch-Brite™ Clean & Shine Pad
2-in-1 daily cleaning pad for low-speed scrubbers that gradually increases shine with repeated use.



3M™ White Super Polish Pad 4100
Ideal for removing soil and scuff marks with minimal dulling. Also used to polish wood floors.



3M™ Eraser Burnish Pad 3600
Removes black marks and returns gloss in fewer passes than other pads while producing less dust. Ideal for harder finishes and high traffic areas. Excellent durability and minimal finish removal.



3M™ TopLine Speed Burnish Pad 3200
Optimizes UHS burnishing on a wide variety of finishes. Combines black mark removal and gloss generation in one pad.



3M™ Sky Blue Hi-Performance Burnish Pad 3050
Restores gloss to dull floors. Designed for frequent burnishing with less dust, point buildup and burning.



Scotch-Brite™ Sienna Diamond Floor Pad Plus
Diamond-coated floor pads clean and condition worn and dull marble, terrazzo, slate and polished concrete, bringing it to a medium gloss.



Scotch-Brite™ Purple Diamond Floor Pad Plus
Diamond-coated floor pads further enhance the appearance of terrazzo, slate and polished concrete.



3M™ Black Stripper Pad 7200
Standard of the industry. Consistent proven performance. Long pad life.



Scotch-Brite™ Surface Preparation Pad
Heavy-duty scrubbing for top coat removal prior to recoating.



3M™ TopLine Autoscrubber Pad 5000
Scrubs and cleans. Open construction resists clogging. Ideal for autoscrubbers.



3M™ Red Buffer Pad 5100
Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.




3M™ Natural Blend Tan Pad 3500
Blend of natural and synthetic fibers. Ideal for harder finishes and high traffic conditions. Removes marks and scuffs while polishing.




3M™ Natural Blend White Pad 3300
Blend of natural and synthetic fibers. Excellent results on a wide variety of finishes and traffic conditions. Consistent high gloss with minimal swirl marks.



3M™ Aqua Burnish Pad 3100
Good gloss improvement with exceptional durability and life. The soft finish problem solver.



3M™ Brown Stripper Pad 7100
Conformable stripping pad for uneven floors. Super heavy-duty scrubbing for 2-4 coat removal.



3M™ Blue Cleaner Pad 5300
Heavy-duty scrubbing of floors.



3M™ Red Buffer Pad 5100
Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.



3M™ Tan Burnish Pad 3400
Produces good gloss improvement while removing scuffs and marks. Exceptional durability and life. Ideal for harder finishes and high traffic conditions.


Green Seal

The Green Seal Environmental Innovation program recognizes products that significantly reduce environmental impact through product innovation. 3M™ Floor Pads® are certified by Green Seal® for Environmental Innovation based on a design for significantly improved performance, durability, or both, extending the useful life of the floor pad and reducing solid waste generation.

*3M™ and Scotch-Brite™ Brand Floor Pad families include: 7300, 7200, 7100, 5300, 5100, 5000, 3600, 3500, 3300, 3200, 3100, 3050, 3000, 3400, 3500N, and 3400N.
†Niagara™ Brand Floor Pad families include: 7200N, 7300N, 5300N, and Deep Scrubbing Pad


Greener Solutions

Greener Solutions is a 3M program for 3M™ Floor Pads® that are made with at least 50% post-consumer recycled materials and water-based latex resins. Plus, our packaging is 100% recyclable and made with 50-100% recycled content.

The polyester fiber used to make a range of floor pads* contains a minimum of 50% post-consumer recycled content. The recycled polyester fiber is the same as the recycled fiber used in the 3M™ Niagara™ Brand Floor Pad families include: 3200, 3300, 3400, 3500, 3600, 5000, 5100, Sierra and Purple Diamond Pad.
†Niagara™ Brand Floor Pad families include: 3300N, 3400N, 3500N, 3600N, 5100N, 5400N and 7200N.

Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time of shipment. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.