



## Product Description

3M™ Black Stripper Pad 7200 is a floor maintenance stripping pad made of nylon and polyester fibers in an open textured, non-woven construction. Abrasive particles are dispersed throughout and bonded to the non-woven construction with a durable resin system that permeates the entire pad. Unique design and durable construction make these pads the industry standard for consistent performance and long life.

- Designed to strip floor finish from floor prior to refinishing
- For use on standard, low speed automatic scrubbers and rotary floor machines (175 - 600 rpm)

## Applications

This product is used with water-based floor finish stripping solutions to remove old soiled floor finishes and sealers. The product is also used to clean heavily soiled hard surface floors such as concrete when used with appropriate cleaning chemicals. The product is intended for use on standard, low speed automatic scrubbers and rotary floor machines. For use on finish-coated flooring such as sheet vinyl, vinyl tile, marble, terrazzo or concrete.

## Features and Benefits

Uniform coating throughout every 3M™ floor pad reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life. Pads are reversible and will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance. Exacting standards for quality mean thickness uniformity from edge to edge and pad to pad are exceptional, resulting in consistent performance without pad wobble or machine vibration. The precise center-hole placement and roundness of the pads also contributes to the smooth operation which extends pad life and may help reduce operator fatigue.

### Quick Links

[Facilities Website](#)  
[Safety Data Sheets \(SDS\)](#)

Some of these links lead to web-based resources that are not product-specific.

## Packaging and Marking

Each carton shall be labeled to identify the contents by product name, size, quantity and manufacturer. Each pad shall be printed with the manufacturer's name.

## Standard Sizes

Circular discs and other shapes are available in a variety of common sizes. Pads are nominally one inch thick.

## Pad Use and Cleaning

Dust mop or sweep floors prior to scrubbing with stripping or cleaning solution and floor pad. Pick up dirty solution with a mop, wet vacuum, or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic.

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked soil or finish prior to hosing out.

## Storage

Store indoors in original packaging and under normal facility conditions.

## Product Characteristics

3M™ Black Stripper Pad 7200		Test Method
<b>Fiber Type</b>	Nylon/Polyester	N/A
<b>Weight (4 in. by 6 in.)</b>	30.5 g	CCD0015
<b>O.D. Dimension</b>	Designated Size ± 1/16 in.	CCD0004
<b>Thickness</b>	3/4 in. nominal	CCD0002
<b>Alkali Resistance (Tensile Retention)</b>	99%	CCD0005,6
<b>Aggressiveness</b>	2.8 g	CCD0020
<b>Packaging Recycle Content</b>	50-100% recycled content	N/A



3M™ Black Stripping Pad 7200 is certified by Green Seal® for Environmental Innovation based on a design for significantly improved initial and mid-life performance compared to competitive products, extending the useful life of the floor pad and reducing solid waste generation. GreenSeal.org.

**Explanation of Signal Word Consequences** **DANGER**

Indicates a hazardous situation which, if not avoided, will result in serious injury or death.

 **WARNING**

Indicates a hazardous situation which, if not avoided, could result in serious injury or death.

 **DANGER**

To reduce the risks associated with inhalation of or exposure to contaminants:

- DO NOT use this product on any asbestos-containing material.

 **WARNING**

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

**Health and Safety** **CAUTION**

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to [3M.com/SDS](https://www.3m.com/SDS), or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturers' instructions for safe operation.

**Technical Information**

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or

experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the **Customer Service Department at 1-800-852-9722**.

**Product Use**

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

**Warranty**

3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**Limited Remedy**

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**No Extension of Warranty**

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

**Limitation of Liability**

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



# Choose the right floor pad for the job.

Maintenance Operation	Equipment Speed	First Choice	Alternate Choices
<b>Stripping</b> To remove finish, sealer and contaminants from the floor surface.	Rotary or Automatic Low Speed 175-600 RPM	<b>3M™ High Productivity Pad 7300</b> Our most aggressive stripping pad. Unique open construction resists loading and clogging. For fast removal of finish and proven consistent stripping.	<b>3M™ Black Stripper Pad 7200</b> Standard of the industry. Consistent proven performance. Long pad life.
	Rotary or Automatic Low Speed 175-600 RPM	<b>Scotch-Brite™ Surface Preparation Pad Plus</b> Long-lasting, high performance scrubbing pad for top coat removal prior to recoating.	<b>Scotch-Brite™ Surface Preparation Pad</b> Heavy-duty scrubbing for top coat removal prior to recoating.
	Rotary or Automatic Low Speed 175-600 RPM	<b>Scotch-Brite™ Clean &amp; Shine Pad</b> 2-in-1 daily cleaning pad for low-speed scrubbers that gradually increases shine with repeated use.	<b>3M™ TopLine Autoscrubber Pad 5000</b> Scrubs and cleans. Open construction resists clogging. Ideal for autoscrubbers.
<b>Buffing</b> To remove scuffs and black heel marks and enhance floor appearance.	Rotary Low Speed 175-600 RPM	<b>3M™ White Super Polish Pad 4100</b> Ideal for removing soil and scuff marks with minimal dulling. Also used to polish wood floors.	<b>3M™ Red Buffer Pad 5100</b> Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.
	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	<b>3M™ Eraser Burnish Pad 3600</b> Removes black marks and returns gloss in fewer passes than other pads while producing less dust. Ideal for harder finishes and high traffic areas. Excellent durability and minimal finish removal.	<b>3M™ Red Buffer Pad 5100</b> Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.
<b>Burnishing</b> To remove scuffs and marks, repair finish and improve gloss and image clarity.	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	<b>3M™ TopLine Speed Burnish Pad 3200</b> Optimizes UHS burnishing on a wide variety of finishes. Combines black mark removal and gloss generation in one pad.	<b>3M™ Natural Blend Tan Pad 3500</b> Blend of natural and synthetic fibers. Ideal for harder finishes and high traffic conditions. Removes marks and scuffs while polishing.
	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	<b>3M™ Sky Blue Hi-Performance Burnish Pad 3050</b> Restores gloss to dull floors. Designed for frequent burnishing with less dust, point buildup and burning.	<b>3M™ Natural Blend White Pad 3300</b> Blend of natural and synthetic fibers. Excellent results on a wide variety of finishes and traffic conditions. Consistent high gloss with minimal swirl marks.
<b>Soft Finish</b>	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	<b>Scotch-Brite™ Sienna Diamond Floor Pad Plus</b> Diamond-coated floor pads clean and condition worn and dull marble, terrazzo, slate and polished concrete, bringing it to a medium gloss.	<b>3M™ Aqua Burnish Pad 3100</b> Good gloss improvement with exceptional durability and life. The soft finish problem solver.
	Rotary, Automatic, Electric, Battery or Propane Low to Ultra High Speed 175-1500 RPM & Above	<b>Scotch-Brite™ Purple Diamond Floor Pad Plus</b> Diamond-coated floor pads further enhance the appearance of terrazzo, slate and polished concrete.	<b>3M™ Tan Burnish Pad 3400</b> Produces good gloss improvement while removing scuffs and marks. Exceptional durability and life. Ideal for harder finishes and high traffic conditions.
<b>Stone Floor Conditioning</b> To clean and condition worn and dull stone floors.	Rotary, Automatic, Electric, Battery or Propane Low to Ultra High Speed 175-1500 RPM & Above		
	Rotary, Automatic, Electric, Battery or Propane Low to Ultra High Speed 175-1500 RPM & Above		

**Green Seal**

The Green Seal Environmental Innovation program recognizes products that significantly reduce environmental impact through product innovation. 3M™ Floor Pads\* are certified by Green Seal® for Environmental Innovation based on a design for significantly improved performance, durability, or both, extending the useful life of the floor pad and reducing solid waste generation.

\*3M™ and Scotch-Brite™ Brand Floor Pad families include: 7300, 7200, 5000, 5100, Purple Diamond Floor Pad Plus, TopLine Speed Burnish Pad, TopLine Super Polish Pad, TopLine Clean & Shine Pad, Niagara™ Brand Floor Pad families include: 7400N, 7300N, 5300N, and Deep Scrubbing Pad.



**Greener Solutions**

Greener Solutions is a 3M program for 3M™ Floor Pads\* that are made with at least 50% post-consumer recycled materials and water-based latex resins. Plus, our packaging is 100% recyclable and made with 50-100% recycled content.

The polyester fiber used to make a range of floor pads\* contains a minimum of 50% post-consumer recycled content. The recycled polyester fiber is the same as the fiber used to make the recycled polyester fiber. 3M™ Brand Floor Pad families include: 3200, 3300, 3400, 3500, 3600, 5000, 5100, Sienna and Purple Diamond Pad. Niagara™ Brand Floor Pad families include: 3300N, 3400N, 3500N, 3700N, 5100N, 5400N and 7200N.



**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.