



Quick Links
[Resource Library](#)
[Safety Data Sheets \(SDS\)](#)
[Video Library](#)

Some of these links lead to web-based resources that are not product-specific.

Product Description

Scotch-Brite™ Surface Preparation Pad Plus is a floor maintenance deep scrubbing pad made of nylon fiber in an open textured, non-woven construction. Specialized abrasive particles are bonded to the non-woven construction with a durable resin system. SPP Plus provides aggressive deep scrubbing performance while leaving a smooth surface to re-coat. Unique abrasive and construction scuffs surface to create optimal bonding of finish and conforming to uneven surfaces.

- Designed to remove soiled top layers of floor finish using water or neutral cleaner instead of harsh stripping chemicals
- For use on standard, low speed (175 - 600 rpm) automatic scrubbers, rotary machines and rectangular (orbital) floor machines.

Applications

This product is for use with neutral cleaner or water to remove layers of soiled or damaged floor finish without the slippery surface and harsh chemicals associated with standard floor strippers. For use on finish-coated flooring such as wood, sheet vinyl, vinyl tile, marble, terrazzo or concrete.

Features and Benefits

- Specialized manufacturing process reduces the number of knots and clumps, which eliminates scratching of floors while providing greater consistency and extended pad life.
- Pad will not be significantly affected by water, detergents, or cleaners normally used for floor maintenance.
- Unique design reduces clogging during use.
- SPP Plus does not require the use of a backer pad.*
- Exacting standards for quality mean thickness uniformity from edge to edge and pad to pad are exceptional, resulting in consistent performance without pad wobble or machine vibration. The precise center-hole placement and roundness of the pads also contributes to the smooth operation which extends pad life and may help reduce operator fatigue.

Packaging and Marking

Each carton shall be labeled to identify the contents by product name, size, quantity and manufacturer.

Standard Sizes

Circular discs and rectangles are available in a variety of common sizes. Pads are nominally 0.8 inch thick.

Pad Use and Cleaning

Dust mop entire floor prior to scrubbing. Install appropriate sized Scotch-Brite™ Surface Preparation Pad Plus on cleaning equipment. SPP Plus can be used on automatic scrubbers, rotary floor machines, or rectangular (orbital) floor machines without a backer floor pad.* Wet the floor with water or neutral cleaner and scrub the floor to desired result. Both sides of the pad can be used. When desired, pad can be flipped. Pick up dirty solution with a mop, wet vacuum, or automatic scrubber. Rinse floor and let dry prior to recoating or opening to traffic. Pads may be rinsed with water to clean if desired.

* Confirm pad driver compatibility with machine manufacturer before using without backer pad.

Storage

Store indoors in original packaging and under normal facility conditions.

Product Characteristics

Scotch-Brite™ Surface Preparation Pad Plus		Test Method
Fiber Type	Nylon	N/A
Weight (4 in. by 6 in.)	16.83 g	CCD0015
Thickness	0.8 in. nominal	CCD0002
Packaging Recycled Content	50-100% post consumer recycled material	N/A
Color	Maroon	N/A

Scotch-Brite™ Surface Preparation Pad Plus

Explanation of Signal Word Consequences

DANGER

Indicates a hazardous situation which, if not avoided, will result in serious injury or death.

WARNING

Indicates a hazardous situation which, if not avoided, could result in serious injury or death.

DANGER

To reduce the risks associated with inhalation of or exposure to contaminants:

- DO NOT use this product on any asbestos-containing material.

WARNING

To reduce the risks associated with inhalation of or exposure to contaminants:

- Ensure this product is used in the recommended applications with the suggested equipment.
- Do not allow this product to be used by untrained operators.
- Always follow standard safety practices, including wearing appropriate protective apparel and eye protection, while using this product.

Precautionary Summary

Do not use on soft metal and plastic surfaces, painted surfaces, or other surfaces that are easily scratched.

Health and Safety

When handling any chemical products, read the manufacturers' container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to 3M.com/SDS, or by mail or in case of an emergency, call 1-888-364-3577 or 1-651-737-6501. When using any equipment, always follow the manufacturers' instructions for safe operation.

Technical Information

Technical information and data, recommendations, and other statements provided by 3M are based on information, tests, or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed. Such technical information and data are intended for persons with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. The typical values shown should not be used for the purpose of specification limits. If you have questions about this Product, contact the **Customer Service Department at 1-800-852-9722**.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty

3M warrants that each 3M product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Limited Remedy

If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

No Extension of Warranty

In the case of an approved warranty claim, the replacement Product will carry only the remaining term of the original warranty period.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.

Commercial Solutions Division



















3M Center, Building 220-12E-04
St. Paul, MN 55144

1-800-328-0033
3M.com/Facility

© 3M 2018. All rights reserved.
3M and ScotchBrite are trademarks of 3M.
Used under license in Canada.
All other trademarks are property of their respective owners.
Revision B, October 2018. Please recycle.



Choose the right floor pad for the job.

Maintenance Operation	Equipment Speed	First Choice	Alternate Choices
Stripping To remove finish, sealer and contaminants from the floor surface.	Rotary or Automatic Low Speed 175–600 RPM	 <p>3M™ High Productivity Pad 7300 Our most aggressive stripping pad. Unique open construction resists loading and clogging. For fast removal of finish and proven consistent stripping.</p>	 <p>3M™ Black Stripper Pad 7200 Standard of the industry. Consistent proven performance. Long pad life.</p>
	Rotary or Automatic Low Speed 175–600 RPM	 <p>Scotch-Brite™ Surface Preparation Pad Plus Long-lasting, high performance scrubbing pad for top coat removal prior to recoating.</p>	 <p>Scotch-Brite™ Surface Preparation Pad Heavy-duty scrubbing for top coat removal prior to recoating.</p>
Cleaning To remove light soil and other contaminants.	Rotary or Automatic Low Speed 175–600 RPM	 <p>Scotch-Brite™ Clean & Shine Pad 2-in-1 daily cleaning pad for low-speed scrubbers that gradually increases shine with repeated use.</p>	 <p>3M™ TopLine Autoscrubber Pad 5000 Scrubs and cleans. Open construction resists clogging. Ideal for autoscrubbers.</p>
	Rotary Low Speed 175–600 RPM	 <p>3M™ White Super Polish Pad 4100 Ideal for removing soil and scuff marks with minimal dulling. Also used to polish wood floors.</p>	 <p>3M™ Red Buffer Pad 5100 Designed for everyday cleaning and light scrubbing to remove light soil, scuff marks and black heel marks.</p>
Burnishing To remove scuffs and marks, repair finish and improve gloss and image clarity.	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	 <p>3M™ Eraser Burnish Pad 3600 Removes black marks and returns gloss in fewer passes than other pads while producing less dust. Ideal for harder finishes and high traffic areas. Excellent durability and minimal finish removal.</p>	 <p>3M™ Natural Blend Tan Pad 3500 Blend of natural and synthetic fibers. Ideal for harder finishes and high traffic conditions. Removes marks and scuffs while polishing.</p>
	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	 <p>3M™ TopLine Speed Burnish Pad 3200 Optimizes UHS burnishing on a wide variety of finishes. Combines black mark removal and gloss generation in one pad.</p>	 <p>3M™ Natural Blend White Pad 3300 Blend of natural and synthetic fibers. Excellent results on a wide variety of finishes and traffic conditions. Consistent high gloss with minimal swirl marks.</p>
Soft Finish	Electric, Battery, Propane Ultra High Speed 1500 RPM & Above	 <p>3M™ Sky Blue Hi-Performance Burnish Pad 3050 Restores gloss to dull floors. Designed for frequent burnishing with less dust, point buildup and burning.</p>	 <p>3M™ Aqua Burnish Pad 3100 Good gloss improvement with exceptional durability and life. The soft finish problem solver.</p>
	Rotary, Automatic, Electric, Battery or Propane	 <p>Scotch-Brite™ Sienna Diamond Floor Pad Plus Diamond-coated floor pads clean and condition worn and dull marble, terrazzo, slate and polished concrete, bringing it to a medium gloss.</p>	
Stone Floor Polishing To clean and polish stone floors with medium shine in good condition.	Rotary, Automatic, Electric, Battery or Propane Low to Ultra High Speed 175–1500 RPM & Above	 <p>Scotch-Brite™ Purple Diamond Floor Pad Plus Diamond-coated floor pads further enhance the appearance of terrazzo, slate and polished concrete.</p>	 <p>3M™ Tan Burnish Pad 3400 Produces good gloss improvement while removing scuffs and marks. Exceptional durability and life. Ideal for harder finishes and high traffic conditions.</p>
	Rotary, Automatic, Electric, Battery or Propane Low to Ultra High Speed 175–1500 RPM & Above		 <p>3M™ Brown Stripper Pad 7100 Conformable stripping pad for uneven floors. Super heavy-duty scrubbing for 2–4 coat removal.</p>

Green Seal

The Green Seal Environmental Innovation program recognizes products that significantly reduce environmental impact through product innovation. 3M™ Floor Pads* are certified by Green Seal® for Environmental Innovation based on a design for significantly improved performance, durability, or both, extending the useful life of the floor pad and reducing solid waste generation.

*3M™ and Scotch-Brite™ Brand Floor Pad families include: 7300, 7200, 5000, 5100, Purple Diamond Floor Pad, and Scotch-Brite™ Surface Preparation Pad. Niagara™ Brand Floor Pad families include: 3300N, 3400N, 3500N, and Deep Scrubbing Pad.



Greener Solutions

Greener Solutions is a 3M program for 3M™ Floor Pads* that are made with at least 50% post-consumer recycled materials and water-based latex resins. Plus, our packaging is 100% recyclable and made with 50–100% recycled content.

The polyester fiber used to make a range of floor pads* contains a minimum of 50% post-consumer recycled content. The recycled polyester fiber is the same as the fiber used to make 3M™ Scotch-Brite™ Floor Pads. 3M™ Brand Floor Pad families include: 3200, 3300, 3400, 3500, 3600, 5000, 5100, Sienna and Purple Diamond Pad. Niagara™ Brand Floor Pad families include: 3300N, 3400N, 3500N, 3700N, 3800N, 3400N and 7200N.



Product Selection and Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.